

Order Form for the Positioning Frame Adacta-Giò



Order

Quotation

Invoicing Details	Shipping Details
Company name:	Ship to:
Delivery date required://	
Delivery address:	CUSTOMER STAMP AND SIGNATURE
P. Code.: Town:	
Tel.: Fax:	
# Order:/ Date of the Order://	

Pro Medicare srl grants **24 months** warranty on production defects from the date of the first put into service and **12 months** on covers and components subjected to wearing. Warranty is void if the product is used in any other way than stated in the Instruction Manual.

Note: Any request for variation in dimensions, materials and type compared to the standard does not have **CE** marking, therefore the professional user becomes the manufacturer and has the obligation to draw up the technical documentation of the device. *Images are purely illustrative and may not fully reflect reality.*

Standard Configuration

- Adacta titanium satin anodised frame with colored plates
- Adjustable single handlebar with folding backrest tubes
- Reclining mechanism by predetermined plate w/pin 3°, 10°, 18°
- Continuous Tilt in space by pedal: from $\,2^\circ\,\text{up to }\,35^\circ\,\text{(from }\,6^\circ\,\text{up to }\,39^\circ)^1$
- 1 tilt in space can be up-graded of 4° with an increment of the starting inclination of the frame by operating on the positioning holes of the casters forks
- Fixed anti-tip system
- Wheels Kit with brake
- Adjustment of the seat depth
- Height adjustment: high (49 cm from the floor)/ low (43 cm from the floor)*
- *(with 300mm and 500mm wheels only)
- Knee Angle
- Foot Plates
- Simple Calf Strap

□ = Optional with up-charge


Note: If a selection is not made, the product will be delivered in its standard configuration. (See **bold** items)


Rigid Frame Structure	
Frame Color	Titanium satin anodised frame with colored plates:
	O Blue O Pink O Bordeaux

Frame size

(Width measurements are from tube to tube externally, while depth measurements are from back post to footboard engagement)

buck post to jouth	back post to Jootboard Engagement)							
Size	Seat Width (cm)	Depth and adjustments (cm)						
0 1	25	o 32 0 34.5 o 37						
o 2	25	o 36 ◊ 38.5 o 41						
0 3	30	o 32 ◊ 34.5 o 37						
0 4	30	o 36 ◊ 38.5 o 41						
0 5	35	o 36 ◊ 38.5 o 41						
0 6	35	○ 40 ◊ 42.5 ○ 45						
o 7	38	○ 40 ◊ 42.5 ○ 45						





H: seat rails to floor height (see page 4)

Q: length from seat rails to footplate (see page 4)

C: push handles height to floor = 110 cm

M: push handles height from seat rails (see page 2)

Mod.Ord.Ada.Giò S.P. EN Rev.7 10/2025 1/5

FRAME OPTIONS							
Castors							
◊ 150mm (6")	poly grey	O b	lack	175mm (7") poly	O grey	O black
Posterior Whe				·	,,,,		
♦ 300mm (12") p		narking hrake	lever				
O 300mm (12") po		-					
O 300mm (12") pi	-			r			
□ 300mm (12") p							
□ 300mm (12") p	-						
□ 300mm (12") p	neumatic <i>gre</i>	y with drum b	rake				
□ 300mm (12") p	oly <i>black</i> witl	n drum brake a	and parking	g brake lever			
□ 300mm (12") p	oly <i>grey</i> with	drum brake a	nd parking	brake lever			
□ 300mm (12") p	neumatic <i>gre</i>	y with drum b	rake and p	arking brake lever			
□ 400mm (16") p	oly <i>black</i> wit	h parking brak	e lever (a	nly 45 cm height)			
□ 400mm (16") p	oly <i>black</i> witl	n drum brake	(only 45	cm height)			
□ 400mm (16") p	oly <i>black</i> witl	n drum brake a	and parking	brake lever (only 45 cm	height)		
□ 500mm (20") p	oly <i>grey</i> with	out handrims	with parkin	g brake lever			500mm (20")la a ala
□ 500mm (20") p	neumatic <i>gre</i>	y without han	drims with	parking brake lever		□ nandrims for	500mm (20") wheels
□ 500mm (20") p	neumatic <i>gre</i>	y with handrir	ns with dru	ım brake			
□ 500mm (20") p	oneumatic <i>gr</i>	ey with handri	ms with dr	um brake and parking bra	ke lever		
Knee Angle							
□ <u>not required</u> *			_	The state of the s			
			7)				
□ RH □ LH				-//			3
*knee angle and foo	otrest	Angle ◊ RH	90° ◊ LH	Angle 75° ORH OLH	Elevating	g (with teethed mechan \Box RI	ism) from 80° up to 180° with a gap of 1 $$
Footrest		.	<u> </u>				
♦ footplates	O fo	otboard	П	slotted (on footplates only)	for intra-ex	tra rotation of 15°)	
padding and cove				divided □ one			
Back Posts	· ··· ··cuci··ci j··c				p.eee		
♦ Folding down	hack nosts i	vith adjustabl	e anale hai	ndlehar			
O Kit for fixed pu	-	vitii uujustubi	_	neight M push handles equal :	to 63 cm		
☐ Kit for telesco		e adiustable si			10 03 0111		
	-	-	_	k adjustment 10 cm)			
☐ Kit for angle a							
☐ Quick-release	-			alid for crash test)			
Tilt in space	•		<u> </u>	,			
♦ with pedal	O with	lever					
Anti-tip syster	m						
♦ fixed	_						
□ detachable							
				RAME ACCESSO	DIEC		
Soat Baso, Nati	. The weeder	s coat bases are	_			a the cost rails	
□ wooden grey (w				or notches of 6 cm for easy m	ovement or	n the seat rails	
	-			rious threaded inserts and cla	mne muet h	ne nerformed by the	customer)
☐ fixed grey wood			ny oj trie var	ious tineuaeu mserts una cia	mps mast t	te perjornica by the t	ustomer)
Abductor wed							
ADDUCTOR WEU	SC Only With I	igiu scut buse			1		
	Size (cm)	□ S □ M		□ removable with lever			e with mounting
	н	7.5 9			7	block	ill
	D	9 10	Γ	Note: if not indicate the abdu	uctor wedge	e will be removable v	vith lever
	L	7.5 9		Please indicate the positi	on of hole	s under the seat	□ standard
	(if not indicated the abductor wedge will be fixed in the standard position)						


Mod.Ord.Ada.Giò S.P. EN Rev.7 10/2025

Vehicle Transportation Kit (according to Do not use the wheelchair as a seat in a vehicle				n 22 ka				
□ only frame height 43 cm and with 300mm (12					alu recomme	ended the use	of a headrest)	
Wooden Supporting Base for Breathing						indea the ase t	oj u neuurest)	
Note: Bulky equipments may lead to a reduction of the				ace with leve	i only			
□ covered in black leather flex								
Please report sizes: Width; Length			_; NOTE					
Note: Pro Medicare Srl reserves the right to check whe	eelchair compa	atibility						
Pedal for barriers								
Side □ RH □ LH								
Leg Support								
Separate Leg Cradle					adjustable	in height and de	epth	
	cm	1	2	3	4	5	6	7
	Н	6	6	10	10	12,5	12,5	15
	L	6	6	9,5	9,5	12,5	12,5	12,5
☐ Calf Panel	1		1 -	l _		in height and de	1	
	cm	1	2	3	4	5	6	7
	H	8 17	8 17	10	10	12	12	15
□ Doddod colf strop	L	17	17	23	23	26,5	26,5	25
□ Padded calf strap	cm	1	2	3	4	5	6	7
	Н	11	11	11	11	11	11	11
	L	20	20	26	26	31	31	34
Cover for Knee Angle joint RH LH		Cove	er for legre	st tube	□ RH □	LH		
Armrest								
☐ Height adjustable flip back tubular armi (L = 25 cm)	rests/inclina	ation max	5°			Ę	L	
☐ Kit of ABS laterals multi-adjustable, det in width and depth with 2.5 cm gap	achable and	d w/multi	-adjustable	arm suppo	ort			
make a selection:	make a sel	ection:				6		
O small arm support (from 1 to 5) (dimensions: 5 cm x 25 cm)	O short ve	rtical bar (f	rom 22 cm to	o 31 cm*)				
O large arm support (from 6 to 7) (dimensions: 6 cm x 30 cm)			om 29 cm to est to the sea			, ,	I	
☐ Multi-adjustable and detachable hips a	nd arms pos	sitioning k						
 pelvis: width, depth, height, adduction/abdu arm support: width, depth, height, inclinat For independent adjustments referring to the v The armrests and the hip guides are assembled possibilities to be modified 	ion, intra/ext	tra-rotatior o is 3 cm	-		chout			
□ small (from frame size 1 up to 4) (armrests dimensions: 8 cm x 22 cm) (hips guide dimensions: 25 cm x 10 cm with	n slot of 5 cm)						
☐ <u>large</u> (from frame size 5 up to 7) (armrests dimensions: 10 cm x 30 cm) (hips guide dimensions: 30 cm x 12 cm with	h slot of 7.5 c	cm)					-	PATENTED
Tray (recommendation for choice: size 1 for Gid	-		Giò size 3 an	nd 4, size 3 fo	or Giò size 5	5, 6 and 7)		
grey wooden with body contouring recess and edges	w	ith 🗆 '	w/lateral flip	1		Type of	hardware	
□ standard option			detachable					17
☐ larger option for daily activities		:16 =	w/lot! fi:					
□ transparent with body contouring recess and edges (only standard option)			w/lateral flip detachable		late	ral flip	detac	hable
Padding □ upper □ lower								

Mod.Ord.Ada.Giò S.P. EN Rev.7 10/2025 3/5

sta	andard option	on dimen	sions
	Size (cm)	Р	L
	1	40	48
	2	45	58
B L	3	50	66

_	орол				
	Size (cm)	Р	L	В	Α
	1	40	48	28	13
	2	45	58	35	15
	3	50	66	40	19



Size (cm)	Р	L	В	Α
1	45	52.5	28	13.5
2	50	62.5	36	15.5
3	55	71	42	19.5

VERSA-FIXATIS FASTENERS

☐ **Pelvic Belt** with 2 fixing points and 2 adjustments with plastic side squeeze buckle



cm	□ XS	□ S
H (pad height)	4.5	5.5
L (pad length)	12	17

□ **Pelvic Belt** with 2 fixing points and 2 adjustments with metal push button buckle



cm	□ S	□ M
H (pad height)	6	7
L (pad length)	17	22

☐ **Pelvic Belt** with 4 fixing points and 2 adjustments with metal push button buckle



cm	□ S	□ M
H (pad height)	6	7
L (pad length)	17	22

OTHER ACCESSORIES



Canopy adaptor included ☐ Blue ☐ Pink ☐ Bordeaux



Foot Muff \square Blue \square Pink \square Bordeaux



□ Rain cover



□ Basket

FRAME DIMENSION AND FEATURES							
Size	1	2	3	4	5	6	7
Load (kg)/Frame Weight* (kg)	30/12.6	30/12.8	50/13.4	50/13.6	50/14.1	50/14.5	50/15.1

* Weight of the frame, including wheels, knee angle and footplates as standard configuration

Weight and overall dimensions (cm) of the frame with backrest tubes folded down, footrest and posterior wheels detached

9	` '			•	•		
Size	1	2	3	4	5	6	7
Length	64	66	64	66	66	68	68
Width	38	38	42	42	48	48	51
Height	64	64	65	65	66	66	67
Weight (kg)	9.4	9.6	10.1	10.3	10.7	11.1	11.5

Note: The length dimensions, referred to the average values, are subjected to the variations due to the displacement of the wheel plates. The values reported are intended for the standard configuration

Width (cm)								
Size 1 2 3 4 5 6						7		
300mm	standard	43	43	48	48	53	53	56
wheel	w/drum brake	44	44	49	49	54	54	57
400/500mm	standard	45	45	50	50	55	55	58
wheel	w/drum brake	48	48	53	53	58	58	61

Mod.Ord.Ada.Giò S.P. EN Rev.7 10/2025 4/5

Pivot Width (cm)	66	66	69	69	72	72	75
Q*(min-max) Height Seat rail to footplate (cm)*	13-20	13-20	13-23	13-23	13-23	13-26	13-26
H Seat rail to floor (cm)**		43 and 49 with 300/500mm posterior wheels and 150/175mm castors 45 with 400 mm posterior wheel and 150/175 castors					
Max Slope	7°						
Note: * The value Q, referred to 90° footrest hanger, can be increased of about 5-7 cm by using the 75° hanger ** The value H has been detected outside the seat tube at the plate of the tilt mechanism; the frame will be delivered with H=43 cm							
Max length (cm) with 75° hanger							
Size	1	2	3	4	5	6	7
300mm wheel	86	89	86	89	89	92	92
400mm wheel	87	90	87	90	90	94	94

Note: The length dimensions, referred to the average values, are subjected to variations due to the displacement of the wheel plates. The values reported are intended for the standard configuration

91

97

97

94

NOTE:



500mm wheel

91

PRO MEDICARE S.r.I.

Via Montagna Z.I. Lotto 41-72023 Mesagne (Br)-ITALY Tel: +39-0831-777840

Website: www.promedicare.eu e-mail: sales@promedicare.it

Mod.Ord.Ada.Giò S.P. EN Rev.7 10/2025 5/5