

LEO VIP Order Form

Order Quotation

Invoicing Details	Shipping Details
Company name:	Ship to:
Delivery date required://	
Delivery address:	CUSTOMER STAMP AND SIGNATURE
P. Code: Town:	
Tel.: Fax:	
Order #: Date of the Order:/	

Pro Medicare srl grants **24 months** warranty on production defects from the date of the first put into service and **12 months** on covers and components subjected to wearing. Warranty is void if the product is used in any other way than stated in the Instruction Manual.

N.B.: Any request for variation in dimensions, materials and type compared to the standard defined for the specific user does not have **CE** marking, therefore the professional user becomes the manufacturer and has the obligation to draw up the technical documentation of the device. *Images are purely illustrative and may not fully reflect reality.*

Section A price "OUTDOOR FRAME FOR POSITIONING SYSTEM" + section B "Positioning systems"

(it includes the relative standard configurations)

SECTION A. "OUTDOOR FRAME FOR POSITIONING SYSTEM" (Standard Configuration)

- Leo outdoor frame for positioning system reclining and tilting with gas piston and 43 cm heigth depth adjustable
- Height, tilt-adjustable, folded down backrest tubes and with tiltadjustable single handlebar
- · Anti-tip wheels
- Parking brake lever
- 175 mm (6") poly casters black
- 300 mm (12") posterior wheels black
- Detachable arm support adjustable in height, width and depth for ABS laterals
- 75° swing-away knee angle
- Fixed wooden seat base with slots for seat depth adjustment

SECTION B. "POSITIONING SYSTEMS" (Standard Configuration)

- Inserto Seat Vip pelvis positioning system
- Inserto Back Vip w/multi-tension strap system trunk positioning system
- Capitis Confort head positioning system size M with multiadjustable bracket
- Pelvic belt with plastic buckle size M



SIZE (indicate selection)			
Cushion (width x depth) cm	Backrest (width x height) cm	Frame Size	Quantity
O 40x40 O 40x45	40x45	XS1	
O 42x42 O 42x45	42x45	S	
O 42x45 O 42x50	O 42x45 O 42x50	M	
O 45x45 O 45x50	O 45x45 O 45x50	M1	
O 48x48 O 48x50	48x50	M1*	

*with 1.5 cm spacers on each side

On the following pages it is possible to choose components which are different from those included in the standard configuration and add any accessories

O = Optional without up-charge \Box = Optional with up-charge

Mod.Ord.Leo-Vip S.P. EN Rev.2 10/2025

Posterior Post	Castors															
300mm (12") poly black with drum brake	O 150mm (6") poly <i>black</i>															
13 20 20 20 20 20 20 20 2	Posterior Wheels															
4.00mm (16") poly black with qurb brake (avery 45 cm height)	□ 300mm (12")	poly <i>t</i>	olack wi	ith drum	brake											
400mm (16") poly black with drum brake (anily 45 cm height) 400mm (16") poly black with drum brake and parking brake lever (anily 45 cm height) 500mm (20") poly grey without handdrims with parking brake lever (anily 45 cm height) 500mm (20") poly grey with but handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handdrims wi	□ 300mm (12")	poly <i>b</i>	olack wi	ith drum	brake a	nd park	ing brake	e lever								
□ 4.00mm (16") poly black with drum brake and parking brake lever (only 45 cm height) □ 500mm (20") poly grey without handrims with parking brake lever □ handrims for 500mm (20") preumatic grey with handrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handrims with drum brake and parking brake lever 600mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with	□ 400mm (16")	poly <i>l</i>	black wi	ith parki	ng brake	e lever (d	only 45 cn	n height)								
□ 4.00mm (16") poly black with drum brake and parking brake lever (only 45 cm height) □ 500mm (20") poly grey without handrims with parking brake lever □ handrims for 500mm (20") preumatic grey with handrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handrims with drum brake and parking brake lever 500mm (20") pneumatic grey with handrims with drum brake and parking brake lever 600mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with handrims with drum brake and parking brake lever 700mm (20") pneumatic grey with	□ 400mm (16")	poly <i>b</i>	olack wi	ith drum	brake (d	only 45 ci	n height)									
	□ 400mm (16")	poly <i>k</i>	olack wi	ith drum	brake a	nd park	ing brake	e lever (d	only 45 cm height)							
Plat and Shape Plat									, , ,							
						•										
Sommi (20") pneumatic grey with handrims with drum brake and parking brake lever					handrim	ns with o	drum bra	ıke								
Name Angle 90° swing away ORH OLH									parking brake lever							
Name Side Size																
Padded Calf Strap	<u></u>	6	S													
Padded Calf Strap																
Padded Calf Strap										(è						
Padded Calf Strap			3								//					
Padded Cali Strap	Λn	رمام ۵۱	l ∩° swind	n-2W2V							Ħ	Þ				
Pootrest	All								<u>Vertical</u>	l elev	ating an	id telesc	<u>opic</u>			
Ground G	Footrast	RH DLH														
Separate Leg Cradle																
Separate Leg Cradle							tpiates p	adding 🗆 Tootboard padding								
Flat Arm Support (2) (pad only) Flat arm Support (3) (pad only) Flat arm Support (3) (pad only) Flat arm Support (4) (pad only) Flat arm Support (5) (pad only) Flat arm Support (5) (pad only) Flat arm Support (6) (pad only) Flat arm Support (7) (pad only) Flat arm Support (8) (pad only) Flat																
Flat Arm Support ② (pad only) Flat Contoured on both sides Arm Support ② (pad only) Flat Contoured on both sides Arm Support W/brackets Flat Contour	☐ Separate Leg (Cradle	e			□ Ca	lf Panel				□ Pa	dded Ca	lf Strap			
Flat arm support w/brackets	Arm support															
Cm S M L W _{BH} W _{LH} H 10 10 12 H 10 10 12 L 25 30 35 Side Size Side Size Side Size Shaped Contoured on both sides and Arm Supports ② (pad only) Shaped Contoured on both sides and Arm Supports ③ (pad only) Shaped Contoured on both sides and Arm Supports ③ (pad only) Shaped Contoured on both sides and Arm Supports ③ (pad only) Shaped Contoured on both sides and Arm Supports ③ (pad only) Shaped Contoured on both sides and Arm Supports ③ (pad only) Shaped Contoured on both sides and Arm Supports ③ (pad only) Shaped Contoured on both sides and Arm Supports ③ (pad only) Shaped Contoured on both sides and Arm Supports ④ (pad only) Shaped Contoured on both sides and A	□ Flat Arm Support ② (pad only)					☐ Flat Contoure	d on	both si	des Arm	Suppor	t ② (pa	d only)				
H 10 10 12 H 10 10 12 H 10 10 12 L 25 30 35 L 25 30 35 L 25 30 35 L 25 30 35 L 25 30 35	☐ Flat arm suppo	ort w	/bracke	ets					☐ Flat Contoured on both sides Arm Support w/brackets							
C 25 30 35	s=2,5		cm	S	М	L	\mathbf{W}_{RH}	\mathbf{W}_{LH}			cm	S	М	L	\mathbf{W}_{RH}	\mathbf{W}_{LH}
Side Size Size Side Size Size Side Size		>	Н	10	10	12			-		Н	10	10	12		
RH	~ ~			25	30	35			Н			25	30	35		
CH		Siz	e							Si	ze					
Flat and Shaped Arm Support ② (pad only) Shaped Contoured on both sides and Arm Supports ② (pad only) Shaped Contoured on both sides and Arm Supports w/brackets Shaped Contoured on both sides and Arm Supports w/brackets Shaped Contoured on both sides and Arm Supports w/brackets Shaped Contoured on both sides and Arm Supports w/brackets Shaped Contoured on both sides and Arm Supports w/brackets Shaped Contoured on both sides and Arm Supports ② (pad only) Shaped Contoured on both sides and Arm Supports ② (pad only) Shaped Contoured on both sides and Arm Supports ② (pad only) Shaped Contoured on both sides and Arm Supports ② (pad only) Shaped Contoured on both sides and Arm Supports w/brackets Side																
Flat and Shaped Arm Support W/brackets										ured	on hot	h sidos a	nd Arm	Sunnor	ts (2)	
Flat and Snaped Arm Support Wybrackets W	☐ Flat and Shaped Arm Support ② (pad only)															
Cm S M L W _{RH} W _{LH} H 10 10 12 L 35 40 48 M 15 17 17 Side Type of Shape Size Side Type of Shape Size Side Type of Shape O palmar O elbow O palmar O palm	☐ Flat and Shape	d Arı	n Supp	ort w/bı	ackets					Suppor	ts					
N	M		cm	S	М	L	W _{RH}	W _{LH}			cm	S	М	L	W _{RH}	W _{LH}
M 15 17 17 M 15 17 17 M 15 17 17	s=2,5 cm		Н	10	10	12			(in)		Н		10	12		
Side Type of Shape Size Side Type of Shape Size O palmar O palmar O palmar O elbow O palmar O palmar O palmar O palmar	L. L.	>							i H							
O palmar O palmar O elbow O elbow O palmar O palmar O palmar O palmar	Cido					1/	l .		Sido			l		1/		
O elbow O palmar O palmar O palmar					Side	0		oi siiap	<u>. </u>		3128					
O palmar O palmar	□ RH								□ RH	_	·					
	□ LH					□LH										

Mod.Ord.Leo-Vip S.P. EN Rev.2 10/2025 2/4

Head Positioning System						
O Capitis Confort head positioning system size G						
☐ Pair of clamping levers for headrest ang	le adjustment					
Fixing elements						
O Pelvic belt with plastic buckle size L						
Electic Butterfly Harness	□ size M					
Elastic Butterfly Harness	□ size L					
Wooden Supporting Base for Brea	thing Equipment covered in black leatherette					
☐ with maximum breathing equipment din	nensions of: Width: 25cm; Length: 30cm; Height: 10cm					
□ with maximum breathing equipment dimensions exceeding 25x30x10cm In this situation, please indicate: Width; Lenght; Height; NOTE;						
Note : Pro Medicare S.r.l. reserves the right to verify compatibility with the wheelchair; respirators with large dimensions can cause a change in the value of tilt and/or recline						
Wooden Tray						
☐ Rectangular Wooden Tray w/lateral flip	nardware					
☐ Rectangular Wooden Tray w/detachable	□ Rectangular Wooden Tray w/detachable hardware					
□ Rectangular Wooden Tray w/detachable double hardware						
□ Padding for Tray in black leather						
□ Padding for ABS Laterals						
☐ Pair of 1.5 cm spacers per side for ABS Laterals						
□ Drip stand						

M1
100
21.7

Overall dimensions (cm) of the frame with backrest tubes (fixed) folded down, footrest and posterior wheels detached

Size	XS1	S	M	M1			
Length	71	73	83	83			
Width	51	54	54	57			
Height	67	67	68	68			
Weight (kg)	14.5	15.1	15.7	16.7			
Note: The book discrete of conductions and a second conduction of the design of the de							

Note: The length dimensions, referred to the average values, are subjected to the variations due to the displacement of the plates. The values reported are intended for the standard configuration

Width (cm)

	Size	XS1	S	М	M1		
300mm	standard	56	59	59	62		
wheel	w/drum brake	57	60	60	63		
400/500mm	standard	58	61	61	64		
wheel	w/drum brake	61	64	64	67		
Pivot	Pivot Width (cm) 75 75 78 78				78		
Q*(min-max) Height Seat rail to footplate (cm)		28-36	28-36	32-40	32-40		
H** Seat r	rail to floor (cm)	43 with 300mm/500mm wheels and 150mm/175mm casters 45 with 400mm wheels and 150/175mm casters					
Max Slope		7°					

 $\textbf{Note: *} \textbf{The value Q} \text{ , refers to the use } 90^{\circ} \text{ footrest tube and can be increased of about 5-7 cm by using the } 75^{\circ} \text{ hanger } 10^{\circ} \text{ hanger$

Mod.Ord.Leo-Vip S.P. EN Rev.2 10/2025 3/4

^{**} H value is measured from outside seat tube at the tilting plate; the BASE will be delivered with H=43cm

Length (cm)					
	Size		XS1	S	М	M1
	Without knee joint	L	75	75	78	78
300mm wheel	75° Knee Angle	L_{min}/L_{max}	97/104	97/104	100/107	100/107
	90° Knee Angle	L _{min} /L _{max}	93/100	93/100	96/103	96/103
	Without knee joint	L	79	79	82	82
400mm wheel	75° Knee Angle	L _{min} /L _{max}	100/107	100/107	103/110	103/110
	90° Knee Angle	L _{min} /L _{max}	96/102	96/102	99/104	99/104
	Without knee joint	L	84	84	87	87
500mm wheel	75° Knee Angle	L _{min} /L _{max}	103/113	103/113	106/116	106/116
	90° Knee Angle	L _{min} /L _{max}	100/106	100/106	103/109	103/109

 $[\]emph{\textbf{L}}$ = Length of the frame without knee angle joint mechanism;

Note: The length dimensions, referred to the average values, are subjected to variations due to the displacement of the wheel plates. The values reported are intended for the standard configuration

<u>Note</u>



PRO MEDICARE S.r.l.

Via Montagna Z.I. Lotto 41-72023 Mesagne (Br)-ITALY Tel: +39-0831-777840

Website: www.promedicare.eu e-mail: sales@promedicare.it

Mod.Ord.Leo-Vip S.P. EN Rev.2 10/2025 4/4

 L_{min} = Length of the frame with knee angle joint mechanism and footplate positioned backward;

 L_{max} = Length of the frame with knee angle joint mechanism and footplate positioned forward.