



## **ORDER FORM**

Invoicing Details	Shipping Details
Company name:	Ship to:
Delivery date required://	
Delivery address:	CUSTOMER STAMP AND SIGNATURE
P. Code.: Town:	
Tel.: Fax:	
# Order:/ Date of the Order://	

**Pro Medicare srl** grants **24 months** warranty on production defects from the date of the first put into service and **12 months** on covers and components subjected to wearing. Warranty is void if the product is used in any other way than stated in the Instruction Manual.

Note: Any request for variation in dimensions, materials and type compared to the standard does not have CE marking, therefore the professional user becomes the manufacturer and has the obligation to draw up the technical documentation of the device.

Images are purely illustrative and may not fully reflect reality.

## **Standard Configuration**

- Frame Adacta Liga Light anodized satin colour Titanium
- Fixed folding down back posts
- Reclining mechanism by predetermined plate w/pin 3°, 9°, 15°, 22°
- Continuous Tilt in Space by drive lever from 4° up to 30° (from 6° up to 39°)¹
   Tilt in space can be up-graded of 4° with an increment of the starting position of the frame by operating on the positioning holes of the caster fork
- Adjustment of the seat depth
- Height adjustment: High (49 cm from the floor) /low (43 cm from the floor)\*
- Detachable footplates with 75° fixed knee angle
- Fixed Anti-tip system
- Wheels Kit with brake
- Rigid wooden seat base covered leather flex
- Kit of ABS laterals with arm supports
- Versa Inserto Trunk/Pelvis positioning system
- Capitis Headrest
- Fixatis Pelvic Belt



The images are purely indicative and may not reflect the standard configuration

**\Diamond= Standard**  $\bigcirc$  = Optional without up-charge  $\square$  = Optional with up-charge

If a selection is not made, the product will be delivered in its standard configuration										
Frame sizes (Outs	ide tubes Width x Depti	h cm)				Frame Type				
O XS1 (38x46)         O S (41x46)         O M (41x50)         O M1 (44x50)         O L (47x46)         O XL (47x50)         O Rigid O Folding										
□ Pre-assembly of postural components (collars for flat base, backrest attachments, headrest hardware)										
Knee Angle										
Castors	Castors  O 150mm (6") poly grey o black o 175mm (7") poly o grey o black									
Posterior Wheels	S (height 43 cm from se	at to the floor with 300 r	nm and 500 mm wheels;	height 47 cm from seat	to the floor with 600	mm wheels)				
♦ 300mm (12") p	oly grey with park	ing brake lever								
o 300mm (12") p	oly <i>black</i> with par	king brake lever								
o 300mm (12") p	neumatic <i>grey</i> wit	h parking brake lev	er							
	oly <i>black</i> with dru									
□ 300mm (12") p	oly <i>grey</i> with drur	n brake								
□ 300mm (12") p	neumatic <i>grey</i> wit	h drum brake								
□ 300mm (12") p	oly <i>black</i> with dru	m brake and parkin	g brake lever							
□ 300mm (12") p	oly <i>grey</i> with drur	n brake and parking	g brake lever							
□ 300mm (12") p	neumatic <i>grey</i> wit	h drum brake and p	oarking brake lever							
□ 400mm (16") p	oly <i>black</i> with par	king brake lever (d	only 45 cm height)							
□ 400mm (16") p	oly <i>black</i> with dru	m brake <i>(only 45 d</i>	cm height)							
□ 400mm (16") p	oly <i>black</i> with dru	m brake and parkin	g brake lever (on	ly 45 cm height)						
□ 500mm (20") p	oly <i>grey</i> without h	andrims with parki	ng brake lever		□ ha	ndrims for 500mm (20") wheels				
□ 500mm (20") p	neumatic <i>grey</i> wit	hout handrims with	n parking brake lev	er	□ IIa	idillis for 500mm (20 ) wheels				
□ 500mm (20") p	neumatic <i>grey</i> wit	h handrims with d	rum brake							
□ 500mm (20") p	neumatic <i>grey</i> wit	h handrims with dr	um brake and park	ing brake lever						
□ 600mm (24") p	neumatic <i>grey</i> wit	h handrims with pa	rking brake lever							
(NOTE. The tilt in sp	pace is reduced to 20	°, only 47 cm height)	-							

Mod.Ord.Ver.Zeu. EN Rev.17 10/2025 1/3

Anti tin system	<b>◊</b> fixed		
Anti-tip system	□ detachabl	e	
Tilt in space	<b>◊</b> with lever	o with pedal	
Pelvis Positioning System			
♦ Inserto Seat Ba	sico	□ Inserto Seat Mediano	□ Inserto Seat Domino
☐ Waterproof seat cover v	with elastic ba	nd	
Trunk Positioning System			
♦ Inserto Back Effecto Lat	0	ar pushing insert	
O Inserto Back Supporto	Luiii	ar containment insert OKIT OLIT	
Backpost (Note: Push handle	es height 63 cm		
<ul> <li>Kit for telescopic push h</li> <li>Kit for angle adjustable</li> <li>Kit for telescopic and an</li> </ul>	ustable in heig andles with le single handleb igle adjustable	8	sap)

## Accessories

Thoracic Supports for Inserto Back Supporto Please, indicate the type, the shapes and the size desired

moracic supports for miscres	ack supports Thease, maleate the type	e, the shapes and the	c size acsi	, cu				
Type of Bracket	Shape of the Pad			cm	□ size 2	□ size 3	□ size 4	□ size 5
Fixed	Flat	=	<b>→</b>	Н	8	10	12	12
□ RH □ LH	□ RH □ LH			L	8.5	10.5	13.5	16.5
Swing-Away	Contoured	·MD		cm	□ size 2	□ size 3	□ size 4	
□ RH □ LH	□ RH □ LH			Н	8	10	12	
			•	L	12.5	14.5	17.5	

**Thoracic Supports for Inserto Back Effecto Lato** Please, indicate the type, the shapes and the size desired

moracic supports for inscrete	Dack Lifecto Lato Tieuse, muicute tile	type, the shapes and t	LITE SIZE	uesiie	u			
Type of Bracket	Shape of the Pa		cm	□ size 2	□ size 3	□ size 4	□ size 5	
Fixed	Flat	1		Н	8	10	12	12
□ RH □ LH	□ RH □ LH		→[	L	10	12	15	18
Swing-Away	Contoured	"MDS		cm	□ size 2	□ size 3	□ size 4	
□ RH □ LH	□ RH □ LH		<b>→</b>	Н	8	10	12	
Detachable	Bracket shape *(for the selection see	Technical Information)		L	14	16	19	
□ RH □ LH	type A: □ RH □ LH type	B: □ RH □ LH	_					

Pedal for barriers 🗆 F	Padding for ABS Laterals □ RH □ LH									
☐ Vehicle Transportation	Abductor wedge only with rigid seat base									
(Only frame height 43cm		cm	□S	□М		1				
*according to the ISO 7176-1. the weight of the user is lowe		Н	7.5	9	□ removable with lever					
Lower limb accessories	-M	D	9	10	□ removable with	-				
☐ Separate Calf Support		L	7.5	9	mounting block	ill				
□ Padded Calf Strap			Note: if not indicate the abductor wedge will be removable with lever							
Cover for legrest tube			Please indicate the position of holes under the seat							
Cover for Knee Angle j			(if not indicated the abductor wedge will be fixed in the standard position)							
☐ Padding and cover o	f footplate in leatherett	e	□ standard							
Capitis Headrest Comf	ort size:		not centred □ on the RH □ on the LH							
o Small	<b>◊</b> Medium	o Large	Tray							
Fixatis Pelvic belt 2P.2A. with squeeze plastic buckle size:				☐ Rectangular Wooden Tray w/lateral flip hardware						
o \$	☐ Rectangular Wooden Tray w/detachable hardware									
Fixatis Dynamic Butter	rfly Harness		□ Padding	for T	ray					
□ <b>S</b>	□ <b>M</b>	пТ				<u> </u>				

Sizes armrest and lateral containment (cm)										
Is=2,5	Α	rmrest	<b>*</b>	ABS	Lateral					
	н	5	H	н	13					
	L	33		L	28					

Mod.Ord.Ver.Zeu. EN Rev.17 10/2025 2/3

(No	Technical Features  (Note: The length dimensions, referred to the average values, are subjected to variations due to the displacement of the wheel plates. The values reported are intended for the standard configuration)														
				Heaviest		Maximum	overall di	mensions	in width/l	ength (cm)	)				
Zeı	us Size	Maximum Load (kg)	Frame Weight (kg)	component weight (Supporto Back) (kg)	standard 300mm wheels	300mm wheels w/drum brake	standard 400mm wheels	400mm wheels w/drum brake	standard 500mm wheels	500mm wheels w/drum brake	600mm wheels	Pivot Width (cm)	Max Slope	Seat rail to floor (cm)	
XS1	Rigido	75	19.2	3.6	56/100	57/100	58/100	61/100	58/106	61/106	58/112	75		43/49 with	
731	Chiudibile	75	19.5	5.0	30/100	37/100	30/100	01/100	36/100	01/100	30/112	73		300/500mm	
s	Rigido	75	19.5	3.9	59/100	60/100	61/102	64/102	61/106	64/106	61/112	75		posterior	
,	Chiudibile	75	19.9	3.9	39/100	00/100	01/102	04/102	01/100	04/100	01/112	73		wheels	
м	Rigido	100	19.8	3.9	59/103	60/103	61/104	64/104	61/109	64/109	61/116	78		45 with	
IVI	Chiudibile	75	20.2	5.9	39/103	60/103	61/104	04/104	01/109	04/109	01/110	76	7°	400mm	
M1	Rigido	100	19.9	4.4	62/103	63/103	64/104	67/104	64/109	67/109	64/116	78	,	posterior wheels	
IVII	Chiudibile	75	20.3	4.4	02/103	03/103	04/104	67/104	04/109	67/109	04/110	76		Wilcold	
	Rigido	100	20.1	5.1	65/100	66/100	67/102	70/102	67/106	70/106	67/112	75		47 with	
L	Chiudibile	75	20.5	3.1	03/100	00/100	67/102	70/102	07/106	70/106	07/112	/5		600mm	
XL	Rigido	100	20.3	5.1	65/103	66/103	67/104	70/104	67/109	70/109	67/116	78		posterior wheels	
ΛL	Chiudibile	75	20.8	3.1	03/103	00/103	67/104	70/104	07/109	70/109	07/110	/8		WITEEIS	

	User Parameters		Frame Cushion Size		Supporto Back sizes (cm)				Effecto Lato Back sizes (cm)			izes (cm)
Zeus Size	Pelvis Width (cm)	Seat Depth (cm)	Depth Adjustments (cm)	(W x D) (cm)	Backrest	Height	Shell Width	Trunk Width	Backrest	Height	Shell Width	*Trunk Width
XS1	ts	35-45	from 44 to 52	40x45	3944	44	36	26-34	3945	45	39	w/bracket <b>A</b> 27-38 w/bracket <b>B</b> 22-32
S	r inserts	35-45	from 44 to 52	42x45	4248	48	39	29-37	4245	45	42	w/bracket <b>A</b> 30-40 w/bracket <b>B</b> 25-35
М	ı inner	40-50	from 48 to 56	42x50	4248	48	39	29-37	4250	50	42	w/bracket A 30-40 w/bracket B 25-35
M1	le with	40-50	from 48 to 56	45x50	4550	50	42	32-40	4550	50	45	w/bracket A 33-43 w/bracket B 28-38
L	Adjustable	35-45	from 44 to 52	48x45	4852	52	45	35-43	4855	55	48	w/bracket A 36-46 w/bracket B 31-41
XL	Ac	40-50	from 48 to 56	48x50	4852	52	45	35-43	4855	55	48	w/bracket <b>A</b> 36-46 w/bracket <b>B</b> 31-41



## PRO MEDICARE S.r.l.

Customer Service (+ 39) 0831.777 840

Via Montagna Z.I. Lotto 41-72023 Mesagne (Br)-ITALY
Website: <a href="mailto:www.promedicare.eu">www.promedicare.eu</a> - E-mail: <a href="mailto:info@promedicare.it">info@promedicare.it</a>; <a href="mailto:sales@promedicare.it">sales@promedicare.it</a>

Mod.Ord.Ver.Zeu. EN Rev.17 10/2025 3/3